DUAL REMOTE CONDENSER

FBD Partnership, LP | 866.323.2777 | sales@fbdfrozen.com | fbdfrozen.com

DUAL REMOTE CONDENSER Specifications

CONDENSER DIMENSIONS

Width: 22.0 in (599 mm) Depth: 48.5 in (1232 mm) Height: 23.0 in (585 mm)

ELECTRICAL REQUIREMENTS

208 to 230VAC, single phase; 2 wire, 15 amp, hard wired

SPACE REQUIREMENTS

Front/Back: 30.0 in (762 mm) for proper air flow

WEIGHT 143 lbs (64.9 kg)

AMBIENT TEMPERATURE OPERATING RANGE

-20°F (-29°C) to 120°F (49°C)

REQUIRED FOR INSTALLATION

- Small crane
- R404A refrigerant, up to 26 lbs 8 oz (12.02 kg)
- Wall-mounted electrical junction box
- Up to 100' of electrical conduit min 16 AWG strand 7x30 wire
- Mounting hardware for junction box and remote condenser (depending on local building code)
- Sealant for roof penetration if necessary

OPTIONS

• Can be ordered with 50' or 100' copper line set



ROHS Compliant. FBD strives for continuous improvements and engineering innovations. Equipment design and/or specifications may change without notice. FBD - Frozen Beverage Dispensers . 8161 Interchange Parkway, Suite 115 • San Antonio, TX 78218 • 210.637.2800 • 1.866.323.2777 • Fax: 210.637.2844 • www.fbdfrozen.com • ©2012 FBD Partnership, LP. FBD®, the FBD logo, and "**Everyone Loves Frozen**²⁴" are trademarks of FBD Partnership, LP, all rights reserved.

REMOTE CONDENSER





REMOTE CONDENSER

FBD Partnership, LP | 866.323.2777 | sales@fbdfrozen.com | fbdfrozen.com

REMOTE CONDENSER Specifications

CONDENSER DIMENSIONS

Width: 39.5 in (1003 mm) Depth: 16.8 in (425 mm) Height: 21.0 in (533 mm)

ELECTRICAL REQUIREMENTS

208 to 230VAC, single phase; 2 wire, 15 amp, hard wired

SPACE REQUIREMENTS

Front/Back: 30.0 in (762 mm) for proper air flow

WEIGHT 105 lb (47.6 kg)

AMBIENT TEMPERATURE OPERATING RANGE

-20°F (-29°C) to 120°F (49°C)

REQUIRED FOR INSTALLATION

- Small crane
- R404A refrigerant, up to 13 lb 4 oz (6.8 kg)
- Wall-mounted electrical junction box
- Up to 100' of electrical conduit min 16 AWG strand 7x30 wire
- Mounting hardware for junction box and remote condenser (depending on local building code)
- Sealant for roof penetration if necessary

OPTIONS

• Can be ordered with 50' or 100' copper line set



ROHS Compliant. FBD strives for continuous improvements and engineering innovations. Equipment design and/or specifications may change without notice. FBD - Frozen Beverage Dispensers . 8161 Interchange Parkway, Suite 115 • San Antonio, TX 78218 • 210.637.2800 • 1.866.323.2777 • Fax: 210.637.2844 • www.fbdfrozen.com • ©2012 FBD Partnership, LP. FBD®, the FBD logo, and "**Everyone Loves Frozen**²⁴ are trademarks of FBD Partnership, LP, all rights reserved.